

E-Lite EXP L1



Introduction

The E-Lite EXP L1 is a **single meter run**, custody flow computer with an ultra-low power, 32-bit microprocessor. It is primarily used in **Metering** and **Well Injection Testing**.

Stack DP's may be used to increase the differential pressure range-ability and performance. Additionally, a frequency or analog signal can be accepted from a **Densitometer**.

An optional **Multivariable Module 205 Sensor** may be integrally mounted to the E-Lite to allow accurate determination of **differential pressure, static pressure, and temperature**.

An **Expansion Module** may be purchased to add four (4) additional Analog Inputs, one (1) Analog Output and, three (3) Digital IO's. (Two (2) may be used for Frequency Input.)



E-Lite EXP L1 Details

Specification

32 Bit Processor
7-24 VDC @ 0.3 WATT
NEMA 7, 4X Class 1 Div. 1
Group B, C and D Housing

Display

8 Lines, 16 Characters
64x128 Pixels
Min Max Charting
Minutes, Hours or Days
Automatic Scrolling

Standard Interfacing

Serial Modbus
(1) SD Memory Slot
(2) Analog or (1)RTD Input
(1) Comm. Port-RS232/485
Selectable
(1) Optional Additional RS232 Port
Rosemount Multivariable-
DP, Press., & Temp.
0.075 % Accuracy of
Calibrated Range

Interrogation Upgrade Options

TCP/IP Encapsulated Modbus
GSM/ Radio
Zigbee Radio
Bluetooth
Satellite
Foundation Fieldbus

Applications

Metering
Well Injection Testing
Well Head Measurement
Custody Measurement
Allocation Measurement
Gas Process Plants

Standardization

API, ISO, AGA

Units of Measurement

Metric & US Customary

Metered Products

Crude Oil (5A/6A, 6A, 23A/24A, 24A)
Refined Products (5B/6B, 6B,
23B/24B, 24B)
Specialized Products (6C, 24C)
LPG (New 23/24, Old 23/24, Old 24)
Propane/Propylene Mix
Saturated Steam
Liquid CO₂ (NIST 14)
Butadiene (ASTM 1550A/B, 1550B)
Water
Propylene (API2565)
Ethylene (API2565)

Instrumentation

Orifice Meter (API 14.3/AGA3)
Turbine/ Freq. Meter (AGA7)
SmartCone® (Dynamic)
Other Cone Meters
Annubar™
Wedge
Venturi

11104 West Airport Blvd, Suite 108
Stafford, Texas 77477 USA
T: 281.565.1118
F: 281.565.1119
sales@dynamicflowcomputers.com

Technical Data- E-Lite EXP L1	
POWER	
VOLTAGE RANGE	7-24 VDC
WATTAGE	0.3 WATT
OPERATING CONDITIONS	
UNITS	US
TEMPERATURE	- 40 TO 185 °F
HUMIDITY	100%
HOUSING	NEMA 4X CLASS 1 DIV. 1
DISPLAY	-20 TO 70 °C WIDE ANGLE
FEATURES	
DISPLAY	PLASMA 8 LINES 16 CHARACTER AND GRAPHICS 64x128 PIXELS
PROCESSOR	32-BIT MOTOROLA 68332 @ 16.7 MHz
FLASH ROM	4 MB @ 70 NANO SECONDS
RAM	2 MB @ 70 NANO SECONDS
MULTIVARIABLE	BUILT-IN ROSEMOUNT MULTIVARIABLE TRANSMITTER WITH DIRECT SPI DIGITAL CONNECTION. MAXIMUM UPDATE SPEED ONCE EVERY 109 MILLISECONDS. TEMPERATURE RANGE: - 200 thru 1200 F PRESSURE RANGE: 0 thru 3626 PSIG DP RANGE: 0 thru 250 inches OR 0 thru 1000 inches
RTD/ANALOG INPUT	ONE (1) 3-WIRE RTD INPUT OR TWO (2) 24-BIT ANALOG INPUTS (MAX. 24mA) BUILT-IN BATTERY VOLTAGE READING
SERIAL COMMUNICATION	ONE (1) SERIAL PORT RS-485/RS-232 SELECTABLE ONE (1) OPTIONAL RS-232 SERIAL PORT
COMMUNICATION PROTOCOL	MODBUS
EXPANSION CARD	
ANALOG INPUT	UP TO SIX (6) ANALOG INPUTS (FOUR (4) 4-20 mA and TWO (2) 0-5 Vdc)
FREQUENCY INPUT	TWO (2) CHANNELS SQUARE WAVE 0-6 kHz, SIGNAL > 3V SINE WAVE 0-1200 Hz, SIGNAL > 70mVp-p
SWITCH OUTPUT	CONFIGURABLE AS: OPEN COLLECTOR, SOURCING MODE OR PUSH/PULL Max 200 mA when Sourcing, 300 mA when Sinking 8-28 Vdc Operating Voltage
RELAY OUTPUT	DRY NORMALLY OPEN CONTACT
ANALOG OUTPUT	ONE (1) 16-BITS OPTICALLY ISOLATED OUTPUT 12-28 Vdc
PID CONTROL	FLOW LOOP AND PRESSURE LOOP